
SynTape® TFE.130

SynTape® TFE.130 is a grey PTFE adhesive tape with silicone adhesive. The backing thickness is 0.13 mm.

Attributes

The tape TFE.130, with extremely high short-term thermal resistance of up to 260 °C, has excellent gliding properties, provides long service life and good mechanical load capacity, is flame retardant according to UL 510 and listed with flammability of UL 94V0.

Application

When high temperatures, high ageing resistance, good sliding properties and good mechanical load capacity are required. It is often used for the insulation of high-frequency parts.

Delivery forms

- Width: From 2.5 mm, in 0.1 mm increments
- Standard length: 50 m
- Core diameter: 76 mm (3")
- Special widths on request

Glue

Silicone

Adhesive

one-sided

Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.

General	Unit of measure	
Temperature range		up to +260°C
Dielectric strength	kV	11.5
Thermal class		180 °C/ H
Tensile strength	N/cm	80
Elongation at break	%	320
Adhesiveness / Adhesion to steel	N/cm	3.5
Total thickness	mm	0.190
Adhesive		Silicone
Backing thickness	mm	0.130
Backing		PTFE film
Standard colours		grey
Type/ Ordering information		TFE.130

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 01/17

