

---

### 3M™ no. 4646F

3M™ 4646F is a double-sided adhesive tape based on a closed-porous acrylic foam.

---

#### Attributes

3M™ 4646F is a double-sided adhesive tape based on a closed-porous acrylic foam with a red film liner. The good temperature resistance allows parts to be bonded together even before powder coating.

---

#### Delivery forms

- Width: from 2.5 mm in 0.1 mm increments
- Standard lengths: on request
- Core diameter: 76 mm (3")

Special widths on request.

---

#### Base

Acrylate

---

#### Color

Dark grey

---

#### Adhesive

Double-sided

---

#### Storage

Adhesive tapes should always be stored in a cool, dry place at approx. 20-30 °C and 50 % relative humidity. The storage period should not exceed 12 months.

**Product datasheet**

3M™ no. 4646F  
Page 2

SynFlex Elektro GmbH  
Auf den Kreuzen 24  
D-32825 Blomberg Germany  
Telefon +49-5235-968-0  
E-Mail info@synflex.de



The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.  
Updated 01/21

