Product datasheet Intertape® 51588 Page 1 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



Inte	rtan	®	51	50	Q

Intertape® 51588 consists of a polyester film with thermosetting rubber adhesive.

Standards

UL-File-No.: E20780 CSA-File: LR94980

Delivery forms

• Width: from 2.5 mm in 0.1 mm increments

Core diameter: 76 mm (3")Special widths on request

_	-
\sim	
Lυ	IUI

Transparent

Glue

Rubber thermosetting

Adhesive

One-sided

Storage

12 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 $^{\circ}$ C and 50 - 60 $^{\circ}$ C relative humidity. The storage period should not exceed 12 months.







SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



Allgemein	Unit of measure	
Type/ Ordering information		Intertape® 51588
Standard colours		Transparent
Backing		Polyester film
Backing thickness	mm	0.025
Adhesive		Rubber thermosetting
Total thickness	mm	0.056
Elongation at break	%	100
Insulation resistance	ΜΩ	10^6
Electrolyt. corrosion value		1.0 Direct/A, 1
Flammability class		BU 1
Thermal class		130 °C (B)
Dielectic strength	kV	5
Tensile strength	N/cm	44
Adhesiveness / Adhesion to steel	N/cm	5.5





