
Intertape® 51595

Intertape® 51595 is a polyester film- / polyester non-woven tape with acrylate adhesive.

Standards

UL-File-No.: E20780

CSA-File: LR94980

Delivery forms

- Width: from 2.5 mm in 0.1 mm increments
- Core diameter: 76 mm (3")
- Special widths on request

Color

Natural, black

Glue

Acrylate

Adhesive

One-sided

Storage

12 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 12 months.

General	Unit of measure	
Type/ Ordering information		Intertape® 51595
Standard colours		Natural, black
Backing		polyester film / polyester non-woven
Backing thickness	mm	0.089
Adhesive		Acrylate
Total thickness	mm	0.114
Elongation at break	%	30
Insulation resistance	MΩ	10 ⁵
Flammability class		BU 2
Thermal class		155 °C (F)
Dielectric strength	kV	5
Tensile strength	N/25 mm	53
Adhesiveness / Adhesion to steel	N/cm	5.5

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.
Updated 05/24

