Product datasheet Isotape® 4239 Page 1 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



Isotape® 4239

Isotape® 4239 is a fibreglass reinforced polyester tape with a pressure sensitive acrylate adhesive.

Delivery forms

• Width: from 2.5 mm in 0.1 mm increments

Core diameter: 76 mm (3")Special widths on request

Translucent

Glue

Pressure sensitive acrylate

Adhesive

One-sided

Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.





Product datasheet Isotape® 4239 Page 2 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



General	Unit of measure	
Type/ Ordering information		Isotape® 4239
Standard colours		Translucent
Backing		Glass fiber reinforced polyester
Adhesive		Pressure sensitive acrylate
Total thickness	mm	0.180
Elongation at break	%	10
Thermal class		155 °C (F)
Dielectic strength	kV	6
Adhesiveness / Adhesion to steel	N/cm	4.68
Tensile strength	N/cm	392
Backing thickness	mm	0.130





