Product datasheet Isotape® 4350PV3 Page 1 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



## Isotape® 4350PV3

Isotape® 4350PV3 is an adhesive tape based on a laminate of Nomex® and polyester film with acrylate adhesive.

## **Delivery forms**

- Width: from 2.5 mm in 0.1 mm increments
- Core diameter: 76 mm (3")Special widths on request

Color			
White			
Glue			
Acrylate			
Adhesive			
One-sided			

## **Storage**

12 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 12 months.





SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



General	Unit of measure	
Type/ Ordering information		Isotape® 4350PV3
Standard colours		White
Backing		50 μm Nomex® + 25 μm Polyester
Backing thickness	mm	0.090
Adhesive		Acrylate
Total thickness	mm	0.130
Elongation at break	%	10
Dielectic strength	kV	6
Tensile strength	N/cm	47
Adhesiveness / Adhesion to steel	N/cm	4.7
Thermal class		155 °C (F)



