Product datasheet Isotape® 4428PV3-32 Page 1 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



Isotape® 4428PV3-32 consists of a polyimide film with silicone adhesive.

Standards

UL-File-No.: E315249

Delivery forms

• Width: from 2.5 mm in 0.1 mm increments

Core diameter: 76 mm (3")Special widths on request

Color

Transparent brown

Glue

Silicone thermosetting

Adhesive

One-sided

Storage

12 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 $^{\circ}$ C and 50 - 60 $^{\circ}$ C relative humidity. The storage period should not exceed 12 months.







SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



General	Unit of measure	
Type/ Ordering information		Isotape® 4428PV3-32
Standard colours		Transparent brown
Backing		Polyimide film
Backing thickness	mm	0.025
Adhesive		Silicone
Total thickness	mm	0.055
Elongation at break	%	70
Thermal class		200 °C (N)
Dielectic strength	kV	6.5
Tensile strength	N/cm	45.2
Adhesiveness / Adhesion to steel	N/cm	2.4







