Product datasheet Isotape® 51350PV3 Page 1 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



Isotape® 51350PV3 is a polyester film tape with acrylate adhesive.

## **Delivery forms**

- Width: from 2.5 mm in 0.1 mm increments
- Core diameter: 76 mm (3")
- Special widths on request

-	

Yellow, white, black, blue, red, green, transparent.

## Glue

Acrylate

## **Adhesive**

One-sided

## **Storage**

12 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 12 months.





Product datasheet Isotape® 51350PV3 Page 2 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



General	Unit of measure	
Type/ Ordering information		Isotape® 51350PV3
Standard colours		Yellow, white, black, blue, red, green, transparent
Backing		Polyester film
Backing thickness	mm	0.025
Adhesive		Acrylate
Total thickness	mm	0.060
Dielectric strength	kV	6
Elongation at break	%	115
Tensile strength	N/cm	47
Adhesiveness / Adhesion to steel	N/cm	4.2
Thermal class		130 °C (B)





