
3M™ no. 27

3M™ electrical insulating tape no. 27 consists of a fibre glass as a backing with a thermosetting latex adhesive.

Attributes

Elastic, good tear resistance und thermal stability, universal use for thermally stressed insulation (UL-listed to 150 °C). Can be printed.

Application

As a cable fixing, a cover band on coils and transformers and for terminal and crossover insulation.

Delivery forms

- Width: from 2.5 mm in 0.1 mm increments
- Standard lengths: 55 m
- Core diameter: 76 mm (3")
- Special widths on request

Glue

Rubber

Adhesive

one-sided

Storage

Adhesive tapes should always be stored in a cool and dry place at approx. 20 °C and 50-60 % relative air humidity. The storage period should not exceed 6 months.

General	Unit of measure	
Thermal class		130 °C/ B
Dielectric strength	kV	3
Adhesiveness / Adhesion to steel	N/cm	3.3
Elongation at break	%	5
Tensile strength	N/cm	252
Total thickness	mm	0.177
Adhesive		Rubber
Backing		Glass fibre
Standard colours		White
Type/ Ordering information		3M™ electro-insulating tape no. 27

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 01/17

