
SynTape® 1695

SynTape® 1695 consists of a metalized polyester film as a backing with a thermosetting acrylate adhesive.

Attributes

High resistance to chemicals, solvents and moisture.

Application

As a splice and reflector adhesive tape for the identification of fabric defects by sensors, for repairing and splicing thermal insulation tarpaulins and for horticultural planning.

Delivery forms

- Width: from 2.5 mm, in 0.1 mm increments
- Standard lengths: 66 m rolls
- Core diameter: 76 mm (3")
- Special widths on request

Glue

Acrylate

Adhesive

one-sided

Storage

6 months at room temperature. Adhesive tapes should always be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.

General	Unit of measure	
Type/ Ordering information		1695
Standard colours		silver
Backing		Polyester film metalized
Backing thickness	mm	0.025
Adhesive		Acrylate
Tensile strength	N/cm	30
Total thickness	mm	0.070
Elongation at break	%	100
Adhesiveness / Adhesion to steel	N/cm	4.5

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 05/24

