

---

## SynTape® B 108/ P.315

SynTape® B 108/ P.315 is a polyester adhesive tape with good adhesiveness due to the thermosetting rubber adhesive.

---

### Attributes

The adhesive tape B 108/ P.315 has high initial adhesiveness and good mechanical load capacity.

---

### Application

As core and interlayer insulation, final insulation, taping and insulation of transformers, coils and wires, UL approved.

---

### Delivery forms

- Width: From 2.5 mm, in 0.1 mm increments
- Standard length: 66 m
- Core diameter: 76 mm (3")
- Special widths on request

---

### Glue

rubber

---

### Adhesive

one-sided

---

### Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.

General	Unit of measure	
Type/ Ordering information		B 108/ P.315
Standard colours		yellow or black
Backing		Polyester film
Backing thickness	mm	0.050
Adhesive		Rubber
Thermal class		130 °C (B)
Electrolyt. corrosion value		1
Dielectric strength	kV	7
Adhesiveness / Adhesion to steel	N/cm	6
Elongation at break	%	100
Tensile strength	N/cm	70
Total thickness	mm	0.087

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.

Updated 07/20

