Product datasheet SynTape® F/ PX.50 Page 1 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



# SynTape® F/ PX.50

SynTape® F/ PX.50 is a Nomex® polyester adhesive tape with high adhesiveness due to the rubber adhesive.

#### **Attributes**

An enhanced dielectric strength is achieved via laminating the tape with a polyester film. UL approved.

## **Application**

For electrical insulation at high thermal loads and as final insulation.

#### **Delivery forms**

• Width: From 2.5 mm, in 0.1 mm increments

Standard length: 50 m
Core diameter: 76 mm (3")
Special widths on request

|  | <br>_ |
|--|-------|
|  |       |
|  |       |

Rubber

### **Adhesive**

one-sided

#### **Storage**

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20  $^{\circ}$ C and 50 - 60  $^{\circ}$ C relative humidity. The storage period should not exceed 6 months.







SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



| General                          | Unit of measure |                    |
|----------------------------------|-----------------|--------------------|
| Type/ Ordering information       |                 | F/ PX.50           |
| Standard colours                 |                 | cream              |
| Backing                          |                 | Nomex® / Polyester |
| Backing thickness                | mm              | 0.090              |
| Adhesive                         |                 | Rubber             |
| Thermal class                    |                 | 155 ° C/ F         |
| Total thickness                  | mm              | 0.135              |
| Tensile strength                 | N/cm            | 65                 |
| Elongation at break              | %               | 10                 |
| Adhesiveness / Adhesion to steel | N/cm            | 5.5                |
| Dielectic strength               | kV              | 7                  |
| Electrolyt. corrosion value      |                 | 1                  |





