Product datasheet SynTape® H 618/ GL.96 Page 1 SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



# SynTape® H 618/ GL.96

SynTape<sup>®</sup> H 618/ GL.96 is a UL-approved fibre glass adhesive tape with silicone adhesive.

#### **Attributes**

High tear and temperature resistant fabric tape with good resistance to impregnants. Flame retardant according to UL 510.

# **Application**

As electrical insulation of coils and transformers, as final insulation and as coil ends of stators. It is used if high mechanical strength, stress relief and thermal resistance are required.

### **Delivery forms**

• Width: From 2.5 mm, in 0.1 mm increments

Standard length: 50 m
Core diameter: 76 mm (3")
Special widths on request

Glue		
Silicone		
Adhesive		
one-sided		

## Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.







SynFlex Elektro GmbH Auf den Kreuzen 24 D-32825 Blomberg Germany Telefon +49-5235-968-0 E-Mail info@synflex.de



General	Unit of measure	
Type/ Ordering information		H 618/ GL.96
Standard colours		white
Backing		Glass fibre
Backing thickness	mm	0.120
Adhesive		Silicone
Thermal class		180 °C/ H
Flame retardant		UL 510
Electrolyt. corrosion value		1
Dielectic strength	kV	2.5
Adhesiveness / Adhesion to steel	N/cm	2.3
Total thickness	mm	0.170
Elongation at break	%	5
Tensile strength	N/cm	300





