

---

## Isotape® 4350PV3

Isotape® 4350PV3 is an adhesive tape based on a laminate of Nomex® and polyester film with acrylate adhesive.

---

### Delivery forms

- Width: from 2.5 mm in 0.1 mm increments
- Core diameter: 76 mm (3")
- Special widths on request

---

### Color

White

---

### Glue

Acrylate

---

### Adhesive

One-sided

---

### Storage

12 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 12 months.

General	Unit of measure	
Type/ Ordering information		Isotape® 4350PV3
Standard colours		White
Backing		50 µm Nomex® + 25 µm Polyester
Backing thickness	mm	0.090
Adhesive		Acrylate
Total thickness	mm	0.130
Elongation at break	%	10
Dielectric strength	kV	6
Tensile strength	N/cm	47
Adhesiveness / Adhesion to steel	N/cm	4.7
Thermal class		155 °C (F)

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.  
Updated 07/20

Isotape® is a registered trademark of SynFlex.  
Nomex® is a registered trademark of E.I. Du Pont de Nemours and Company.

