
Intertape® 4564

Intertape® 4564 is non-woven polyester tape with a zone coated acrylate adhesive.

Delivery forms

- Width: from 2.5 mm in 0.1 mm increments
- Core diameter: 76 mm (3")
- Special widths on request

Color

Natural

Glue

Acrylate zone coated

Adhesive

One-sided

Storage

12 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 12 months.

General	Unit of measure	
Type/ Ordering information		Intertape® 4564
Standard colours		Natural
Backing		Polyester non-woven
Backing thickness	mm	0.061
Adhesive		Acrylate zone coated
Total thickness	mm	0.165
Elongation at break	%	35
Insulation resistance	MΩ	10 ⁶
Electrolyt. corrosion value		A, 1, 2
Thermal class		130 °C (B)
Dielectric strength	kV	0.5
Tensile strength	N/cm	30
Adhesiveness / Adhesion to steel	N/cm	3.5
UL FILE NO.		20780

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.
Updated 05/24

Intertape® is a registered trademark of Intertape Polymer Group.

