
SynTape® A/ CP.50

SynTape® A/ CP.50 is a slightly creped paper adhesive tape.

Attributes

Special feature of the tape is its good initial adhesiveness on various surfaces due to the ductile rubber adhesive.

Application

Final insulation for the production of motors and coil insulation.

Delivery forms

- Width: From 2.5 mm, in 0.1 mm increments
- Standard length: 50 m
- Core diameter: 76 mm (3")
- Special widths on request

Glue

Rubber

Adhesive

one-sided

Storage

6 months at room temperature. Adhesive tapes should be stored in a cool, dry place at approx. 20 °C and 50 - 60 % relative humidity. The storage period should not exceed 6 months.

General	Unit of measure	
Electrolyt. corrosion value		1
Thermal class		105 °C/ A
Dielectric strength	kV	1
Adhesive		Rubber
Total thickness	mm	0.150
Tensile strength	N/cm	45
Elongation at break	%	9
Adhesiveness / Adhesion to steel	N/cm	2.5
Backing thickness	mm	0.110
Backing		slightly creped paper
Standard colours		cream
Type/ Ordering information		A/ CP.50

The information on this data sheet is based on the information provided by our supplier. It does not represent any specification or agreements regarding conditions or properties. The indicated values are standard values. Deviations from those values due to production and application cannot be excluded. The information on this data sheet is addressed to experts who use it at their own discretion and at their own risk. We do not guarantee results, or accept liability for the indicated specifications or for results obtained based on the specifications. Please contact us for more detailed information. Non-toxic and toxic substances are listed on the safety data sheet.
 Updated 01/17

